



Repeats Not Shown to Scale.

Spirit Millennium Sun Yellow / US 322

Meets or exceeds all ACT® Standards

High Performance Vinyl



*ACT® Registered Certification Marks

Fabric Specifications

Face	100% Vinyl
Backing	100% Polyester
Weight	37.0 oz. per linear yd
Thickness	1.28 mm
Width	54"
Directional	No
Railroaded	No

Additional Attributes

Finish/Treatment	BeautyGard® Oil Resistant
BeautyGard®	Yes
Oil Resistant	Yes
Antibacterial	Yes
Antimicrobial	Yes
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Mildew Resistant	Yes
Sulfide Stain Resistant	Yes

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Performance Characteristics

Abrasion Resistance ASTM D4157	1,500,000 double rubs*
Tensile Strength 191A-5100	Warp: 65.0 lbs. Fill: 60.0 lbs.
Tear Strength 191A-5136	Warp: 14.0 lbs. Fill: 12.0 lbs.
Seam Slippage	Warp: 25.0 lbs. Fill: 20.0 lbs.
Colorfastness to Crocking 191A-5651	Dry: Good Wet: Good
UV Resistance SAE J1885	225.6 hours
Adhesion CS-273-65	Warp: 3.0 lbs. Fill: 3.0 lbs.
Blocking 191A-5872	3
Cold Crack 191A-5874	-20° F
Flex CS-273-65	15,000 cycles

Flammability**

CAL TB 117-E	Passes
NFPA 260	Class 1
UFAC	Class 1
Federal Aviation Specification	Passes
Federal Specification	Passes
FMVSS 302	Passes

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

** This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.
Final determination of the suitability of this product for an application rests with the user.

Toll Free **1.800.841.8111**

Visit us at **BurchFabrics.com**